



Das Original

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

Date of issue: 05.07.2024

Revision date: -

Version/Replaced version: 1.0/-

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Part B LiqRep Metal - Resin  
 Product code : B53.810

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
 Use of the substance/mixture : Two-component glue: resin

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer (Germany)

ElringKlinger AG  
 Max-Eyth-Straße 2  
 72581 Dettingen/Erms - Germany  
 T +49 (0)7123 724 799  
[det.iam.sdb@elringklinger.com](mailto:det.iam.sdb@elringklinger.com)

##### Supplier

##### Manufacturer (England)

Elring Parts Ltd  
 Unit 2, Derwent Court  
 Earlsway Team Valley Trading Estate  
 Gateshead  
 Tyne and Wear  
 NE11 TF - England  
 Sales T +44 191 4915678 - F +44 191 4875001  
[sales@elringparts.co.uk](mailto:sales@elringparts.co.uk)

Safety Data Sheet: DLAC Dienstleistungsagentur Chemie GmbH, E-mail: [sds@dlac-gmbh.de](mailto:sds@dlac-gmbh.de)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number
Germany	Giftinformationszentrum (GIZ-Nord) Universitätsmedizin Göttingen - Georg-August-Universität	Robert-Koch Straße 40 37075 Göttingen	+49 551 19240

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to GB CLP

Skin corrosion/irritation, Category 2 H315  
 Serious eye damage/eye irritation, Category 2 H319  
 Sensitisation - Skin, category 1 H317  
 Hazardous to the aquatic environment - Chronic Hazard, Category 2 H411

Full text of H-phrases: see section 16

##### Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to GB CLP

Hazard pictograms (CLP) :



GHS07 GHS09

Signal word (CLP) : Warning

Hazardous ingredients : Bis-[4-(2,3-epoxipropoxy)phenyl]propane

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

Hazard statements (CLP)	: H315 - Causes skin irritation H319 - Causes serious eye irritation H317 - May cause an allergic skin reaction H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection. P391 - Collect spillage. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

The mixture does not contain substance(s) classified as PBT or vPvB in concentrations above 0.1%. The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS No) 1675-54-3 (EC No) 216-823-5 (Index No) 603-073-00-2	80 - 99	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Name	Product identifier	Specific concentration limits according to GB CLP
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS No) 1675-54-3 (EC No) 216-823-5 (Index No) 603-073-00-2	(C ≥ 5) Eye Irrit. 2, H319 (C ≥ 5) Skin Irrit. 2, H315

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell. If possible show him this sheet. Failing this, show him the packaging or label. Never give anything by mouth to an unconscious person. Place the affected person in the recovery position.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. . If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Drink water as a precaution. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing agents that suit the environment. Carbon dioxide. Extinguishing powder. Water spray. For a significant fire: Alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide. Toxic gases and vapors.
--	--

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Use a self-contained breathing apparatus and also a protective suit.

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin and eyes.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : If spilled, may cause the floor to be slippery. Wipe up with absorbent material (for example cloth). Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Keep in suitable, closed containers for disposal. Dispose of in accordance with relevant local regulations.

#### 6.4. Reference to other sections

Exposure controls and personal protection, see section 8. Concerning disposal elimination after cleaning, see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid breathing vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Protect from heat and direct sunlight.

Storage temperature : 10 – 20 °C

Prohibitions on mixed storage : Keep away from food, drink and animal feedingstuffs.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)</b>	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.75 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	4.93 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0.5 mg/kg bodyweight/day
Long-term - systemic effects, dermal	89.3 µg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.87 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	0.006 mg/l
PNEC aqua (marine water)	0.001 mg/l
PNEC aqua (intermittent, freshwater)	0.018 mg/l
PNEC aqua (intermittent, marine water)	0.002 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.341 mg/kg dwt
PNEC sediment (marine water)	0.034 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.065 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	11 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

### 8.2. Exposure controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation to minimize vapour concentrations.
Hand protection	: Wear suitable gloves (EN 374). Nitrile rubber. $\geq 0.35$ mm. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Eye protection	: Chemical goggles or safety glasses (EN 166).
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Respiratory protection with filter type A/P2 (EN 14387).
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	: Liquid. White.
Odour	: Characteristic, slight
Odour threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper/lower flammability or explosive limits	: No data available
Vapour pressure	: No data available
Vapour density	: No data available
Relative density	: No data available
Density	: No data available
Solubility(ies)	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: Thixotropic behaviour
Explosive properties	: None
Oxidising properties	: None

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

### 10.3. Possibility of hazardous reactions

None under normal use.

### 10.4. Conditions to avoid

Protect from heat and direct sunlight.

### 10.5. Incompatible materials

Oxidizing agents.

### 10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature. In case of fire: Carbon dioxide. Carbon monoxide. Toxic gases and vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
	Based on available data, the classification criteria are not met

#### Bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	: Endocrine disruption for human health: The substance/mixture has no endocrine disrupting properties.

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.

#### Bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

LC50 fish	1.2 mg/l 96 h, Oncorhynchus mykiss
EC50 daphnia	1.7 mg/l 48 h, Daphnia magna
EC50 algae	> 11 mg/l 72 h, Scenedesmus capricornutum
NOEC daphnia	0.3 mg/l 21 d, Daphnia magna
NOEC algae	4.2 mg/l 72 h, Scenedesmus capricornutum

### 12.2. Persistence and degradability

#### Bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Persistence and degradability	Not readily biodegradable.
Biodegradation	5 %, 28 d (OECD 301 F)

### 12.3. Bioaccumulative potential

#### Bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Partition coefficient n-octanol/water (Log Pow)	3.242 (25 °C)
---	---------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

Endocrine disruption for the environment : The substance/mixture has no endocrine disrupting properties.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Dispose in a safe manner in accordance with local/national regulations.
Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point. Do not empty into drains.
Waste disposal recommendations	: Empty the packaging completely prior to disposal. When totally empty, containers are recyclable like any other packing.
List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances
Waste code	: The valid LoW waste code numbers are source related. The manufacturer is therefore unable to specify LoW waste codes for the articles or products used in the various sectors. The LoW codes listed are intended as a recommendation for users.

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

#### 14.1. UN number

UN-No. (ADR) : UN 3082  
UN-No. (IMDG) : UN 3082  
UN-No. (IATA) : UN 3082


#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane)  
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane)  
Proper Shipping Name (IATA) : Environmentally hazardous substance, solid, n.o.s. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane)  
Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III, (-)  
Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III, MARINE POLLUTANT  
Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR) : 9  
Danger labels (ADR) : 9



##### IMDG

Transport hazard class(es) (IMDG) : 9  
Danger labels (IMDG) : 9



##### IATA

Transport hazard class(es) (IATA) : 9  
Danger labels (IATA) : 9



#### 14.4. Packing group

Packing group (ADR) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III

#### 14.5. Environmental hazards

Dangerous for the environment : Yes  
Marine pollutant : Yes  
Other information : No supplementary information available.

#### 14.6. Special precautions for user

##### Overland transport

Classification code (ADR) : M6  
Special provisions (ADR) : 274, 335, 375, 601  
Limited quantities (ADR) : 5L  
Excepted quantities (ADR) : E1

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR) : -

### Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Contains no substance(s) listed on UK REACH Annex XIV (Authorisation List).  
Contains no substance(s) listed on the UK REACH Candidate List.

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019 No. 720 as amended by The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Changes compared to the previous version : -

Abbreviations and acronyms:

# Part B LiqRep Metal - Resin

## Safety Data Sheet

according to UK REACH

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	The effective concentration of substance that causes 50% of the maximum response (Median Effective Concentration)
IATA	International Air Transport Association
IMDG	"International Maritime Dangerous Goods Code" for the transport of dangerous goods by sea
LC50	Lethal Concentration to 50 % of a test population (Median Lethal Concentration)
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
NOEC/L	No Observed Effect Concentration/Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent, Bioaccumulative and Toxic substance
PNEC	Predicted No-Effect Concentration
REACH	Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
SDS	Safety Data Sheet
STP	Sewage Treatment Plant
UFI	Unique Formula Identifier
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation - Skin, Category 1
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.